



公差表 (General tolerances)(mm)	
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±Z	

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRT:	
SIZE: A4	mm (inch)
DRAWING NO.:	2ESAW-5.08-XXP-1Y-100A(H)
SCALE:	
REV	1/1

2	Pin header	Copper	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准 / UL Standard:		B	C D
额定电压/电流 / Rated Voltage(V)/Current(A)		300/15	300/10
VDE 标准 / VDE Standard:			
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree		III/3	II/2
额定电压/电流 / Rated Voltage(V)/Current(A)			320/20
额定脉冲电压 (KV) / Rate Impulse Voltage (KV)			4
间距 / Pitch (mm) / 线数范围 / Poles			5.08 / N=02~24P
使用温度范围 / Operating temperature(°C)			-40~+105
符合RoHS环保要求 / Conform to RoHS			Yes


宁波三安电子科技有限公司
 Sanan Electrical Technology Co. Ltd